



# NT10

2-way full range loudspeaker

## Main features

- Components 10" + 1"
- Power Rating 300 Watts
- Coverage 80° x 40°
- Maximum SPL 121 dB

## Electroacoustic features

|                          |                                    |
|--------------------------|------------------------------------|
| Speaker Type             | Compact, passive full range system |
| Acoustic Design          | 2-way, vented design               |
| Components               | 10" + 1"                           |
| Power Rating (RMS)       | 300 Watts                          |
| Power Rating (Program)   | 600 Watts                          |
| Sensitivity              | 96 dB full space                   |
| Maximum SPL              | 121 dB                             |
| Frequency Range (-10 dB) | 50 Hz – 18 kHz                     |
| Nominal Impedance        | 8 Ohms                             |
| Coverage (H*V)           | 80° x 40°                          |

## Physical features

|                        |   |
|------------------------|---|
| Enclosure              | Birch plywood                                 |
| Protection Grill       | Steel grill, powder-coated                    |
| Weight                 |   |
| Standard Colours       | Textured paint, black                         |
| Mounting Points        | 4 × M8 thread                                 |
| Connectors             | 2 × SpeakON                                   |
| Dimensions (W × H × D) | 315 × 474 × 315 mm                            |
| Accessories Optional   | U-bracket UB-1015-BK/<br>U-bracket UB-1019-BK |
| Rigging and Handling   | 1 handle                                      |
| Operating Temperature  | -20°C ~ 60°C                                  |

## Optional features

|                  |                             |
|------------------|-----------------------------|
| Optional Colours | RAL Classic / NCS / Pantone |
|------------------|-----------------------------|

## Dimensions

