



# QX8

Installation 2-way compact loudspeaker

## Main features

- Components 8" + 1"
- Power Rating 150 Watts
- Coverage 100° x 100°
- Maximum SPL 116 dB

## Electroacoustic features

Speaker Type	Installation loudspeaker
Acoustic Design	2-way, vented design
Components	8" + 1"
Power Rating (RMS)	150 Watts
Power Rating (Program)	300 Watts
Sensitivity (1m / 1W)	94 dB full space
Maximum SPL	116 dB
Frequency Range (-10 dB)	65 Hz – 18 kHz
Nominal Impedance	16 Ohms
Coverage (HxV)	100° x 100°

## Physical features

Enclosure	Birch plywood
Protection Grill	Steel grill, powder-coated
Weight	7.3 kg
Standard Colours	Textured paint, black
Mounting Points	4 × M6 thread / 2 × M8 thread
Connectors	4-pin Phoenix terminal
Dimensions (W × H × D)	242 × 380 × 260 mm
Accessories Included	Mounting bracket UB-1008-BK
Accessories Optional	Mounting bracket WM-1004-BK
Rigging and Handling	no handle

## Optional features

Optional Colours	RAL Classic / NCS / Pantone
IP (Weather Protection)	IP55

## Dimensions

